

HUB USB 2.0 + Card Reader 60 in 1

1. Conforms to USB specification Rev. 1.1, 2.0

HUB USB 2.0

- 2. 480Mbps high speed data transmission
- 3. Supports 1 device address and 2 end points adds ports: 3 ports hub
- 4. Supports suspend/normal mode power management
- 5. Supports power management for downstream port devices
- 6. Automatic switching between self/bus powered mode

Slot 1: CF 1, CF 11, Ultra 11 CF, CF Ultimate, Extreme CF, Extreme 111 CF, Extreme 1V CF, CF Elite pro, CF Pro, CF Pro 11, HS CF, XS-XS CF, Hitachi MD, IBM MD, Magic Stor.

Slot 2: XD, XD Type H, XD Type M.

Slot 3: T-flash, Micro SD

Slot 4: MS, MS-MG, MS-Pro-MG, HS-MS-Pro-MG, MS Duo 32MB, MS Duo-MG, MS Pro-Duo-MG, HS-MS Pro-Duo-MG, MS Pro Duo-psp, MS Pro Duo-Gaming. Slot 5: SD, SD-ultra, SD-Compatible, SD-Pro, SD-Ultra 11, SD-Ultra 11 plus, SD-Pleomax, SD-Pro Compatible, SD-Extreme 111 ,SD-Ultra X, SD-Turbo, SD-Super, SD-Max, Mini SD, Mini SD Pro, Mini SD-Pleomax, MMC 1GB, MMC-Pleomax, High Speed MMC, MMC-Plus(8bit), MMC-Plus Turbo, RS MMC, RS MMC-Pleomax, RS MMC-Speed, RS MMC-Max, MMC Pro, MMC Mobile, MMC Mobile-pro Compatible, MMC Mobile-Pocket, SDHC.

English	Italiano	Español	Français	FHU32165
Number of Ports	Numero di porte	Nùmero de puertos	Nombre de ports	N°. 3 x USB - 2.0 (1.1) N° 5 Slot x Card Reader
Transfer rate up to	Velocità di Trasmissione, fino a	Velocita de trasmisiòn hasta	Velocita de transmission e jusqu'à	480 Mbps
Power	Alimentazione	Alimentaciòn	Alimentation	DC Adapter 5V - 1A
Power Led	Spia di Accensione	Spy Energia	Puissance a menè	n. 1
Package Contents	Contenuto della confezione	Contenido del envase	Contenu du paquet	HUB USB 2.0 + Card Reader 60 in 1, DC Apapter 5V - 2A, Cable USB
Os Support	Sistemi Operativi Supportati	Sistemas Operativos Compatibles	Support du Système d'exploitation	Windows 98, NT,2000, 2003, XP, Vista, Mac OS

480 MBPS HIGH SPEED

RUBBER COATED SURFACE

60 CARD READ

EASY PLUG & PLAY



